



Fire brigade control panel extension unit for 7 zones according to DIN 14664, for use with the products VAP1-FES (ART06096) and VAP1-FES 7Z (ART06310). The item is supplied pre-assembled in a suitable IP30 housing. The sheet steel housing, finished in RAL 3000 (fire red), has a door with a glass window and provides a view of the status LED's and operating elements below. The door has a locking insert with locking bolt. With ART03177 FP SSP locking system, an alternative insert is available to accommodate a profile half cylinder.

Individual labeling of the front foils by exchangeable text strips.

The extension unit can be mounted below the VAP1-FES or VAP1-FES 7Z products and screwed and wired via existing openings.

On the extension unit, the following functions can be selectively activated for each area: Live Fire Announcements, Stored Evacuation and alert Announcements, Cancel Automatic Voice Alarm Announcement (Automatic Off).

Technical data:

Model	VAP1-FES ERW 7Z
Power Supply	Via base units VAP1-FES or VAP1-FES 7Z
Dimensions	W415 x H237 x D155mm
Weight	5 kg
Housing	Sheet steel, powder coated, RAL3000
IP degree of protection	IP30
Optional accessories	ART06310 - VAP1-FES 7Z - Fire brigade control panel 7 zones ART06311 - VAP1-FES ERW 14Z - 14- zone extension unit incl.. housing ART06295 - Redundancy module set ART03177 - FP SSP – Locking system for holding profile half cylinder